

## TagScan-Datec, 13.56 MHz Handheld Multitag Plug and Play Reader Module ME-H61xx HHD F/BA

The 13,56 MHz Handheld Multitag Plug and Play Reader Module is an IP65 protected handheld contactless proximity read write device that supports ISO 15693, I-Code®, Tagit®, ISO14443A and ISO 14443B cards. The P&P-Module is equipped with an RS-port and with an antenna and can be connected to a controller or PC very easily.

### Applications

The main applications of the HH Multitag are in the areas of:

- ▶ Retail, Passanger Flow
- ▶ Web Linking, Logistics
- ▶ Public Transport, Ticketing
- ▶ Access Control, Time & Attendance
- ▶ Locking Systems
- ▶ Event Management, Member Cards
- ▶ Parking Systems
- ▶ Automatic Dispensers
- ▶ Toll Systems, Cash Systems
- ▶ General User Identification

### Order Code:

**9110.368**

### TS-H6160HHD F/BA

13.56 MHz Multitag Handheld Reader Module  
 RS232 Interface

- ▶ Option: Wall Mount Holder

### Other Equipment and Options



Office Desktop  
9110.360



IP65 Desktop  
9110.354



Smart Handheld  
9110.374



### Technical data

Technical details of the Multitag P&P Reader	
<b>Size</b>	243 x 90/128 x 60 mm
<b>Supported transponders</b>	ISO 15693: EM 4135, Icode® SLI, LRI512, SRF55VxxP, SRF55VxxS, Tagit® HFI, TempSense, Tagit® Icode®  ISO 14443A Mifare® Std, Mifare® Ultralight, MF1IC70, Mifare ProX, SLE55R16  ISO 14443B: SLE66CL160S, SR176
<b>Interface</b>	RS232 RS422 (on request) RS485 (on request)
<b>Transmission Speed</b>	9600, n, 8, 1 up to 57.6kBAud optionally
<b>Reading distance</b>	up to 40 mm (depending on tag)
<b>Supply voltage</b>	5V/100mA power down mode
<b>Antenna</b>	built in PCB-antenna
<b>Signals</b>	Power LED Read LED and Buzzer
<b>Temperature range</b>	- 20°C up to + 80°C
<b>Approvals</b>	EN300330 1/2

PS: ISO14443A/B Tags reading serial number only